



Sigilant pentru filet Forță Medie 10ml

4306642

AIRPRESS THREAD LOCKER

MEDIUM STRENGTH **10ml**

- Surface dry time 20 min.
- Anaerobic
- General purpose
- Medium Strength
- Thixotropic Viscosity
- Dismountable
- Solvents Resistant
- Environment Resistant

- Thread locker adhesive
- Schroefdraadborgmiddel
- Uszczelniacz do gwintów
- Gewindedichtung
- Scellant pour filetage



Detalii produs

Unitate de înmagazinare	4306642
EAN 13	8712418396744
Greutate (kg)	0.028600
Standard de siguranță	Nu
Rotativ	Nu
Întărit	Nu
Separator de condens	Nu
Regulator de debit	Nu
Blister	Da

Descriere

Description: Airpress Thread Locker is a removable material for preventing nuts, bolts, bearings, fasteners, and screws from loosening. It's able to fill into tiny spaces, making it ideal for use as an anti-rust agent on metals. It's shock and vibration resistant on vehicles, tools, machines, and moving parts. Can be removed with normal hand tools. Resistant against chemicals, oils, and others.

Application Instructions: Wipe off any moisture, oil and dirt on the area to be treated. Shake well before using. Remove the cap. Apply a small amount to the required area/thread. Insert thread immediately to allow for thread locker to penetrate fully. After use, clean the nozzle before re-applying the cap. Before replacing the cap, ensure airspace remains in the bottle to prevent liquid from hardening.

CAUTION: May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Contains: Polyglycol dimethacrylate, bisphenol a fumarate resin, cumene hydroperoxide. Keep out of reach of children. Avoid breathing dust/fume. Wear protective gloves/protective clothing/eye protection/face protection. If inhaled: Move to an area with fresh air and rest in a position comfortable for breathing. If in eyes: rinse cautiously with water for several minutes. Remove contact lenses as needed. Continue rinsing. If skin irritation or rash occurs seek medical attention.

